



The most productive large-format color MFP1—prints up to size E/A0



All your workflow needs in a highproductivity MFP

- Be the fastest—print D/A1-size pages in 21 seconds with dark blacks, neutral grays, and vivid colors¹
- Print out your first page right away thanks to ultra-fast processing and zero warm-up time
- Copy and scan quickly with advanced features—presets, batch scanning, multipage PDFs, and scan to email
- Stay organized and avoid clutter—the integrated 100-page stacker delivers prints and copies neatly collated

A production printer for unattended, low-cost use

- Print your black-and-white drawings at the same cost per page as comparable black-and-white LED MFPs2
- Operate unattended thanks to two heavy rolls of up to 650 ft (200 m) and a total ink capacity of 1,800 ml
- Built for high-volume printing—rely on a robust design to fulfill the most demanding jobs
- Manage projects and control costs effectively, using embedded professional accounting features

Built for rigorous IT demands and top security

- Minimize device-management tasks and costs, using the HP DesignJet Universal Print Driver
- Manage your fleet with ease, while saving time and helping to reduce costs, thanks to HP Web Jetadmin
- Protect and manage confidential jobs securely—retrieve documents at the printer with a personal PIN
- Safeguard confidential information, using a self-encrypting HDD with AES-256, Secure Disk Erase, and IPsec

Eco Highlights

- Half the energy consumption per plot than equivalent black-and-white LED MFPs¹
- ENERGY STAR® qualified and EPEAT Bronze registered²
- Free, convenient HP ink cartridge and printhead recycling³
- FSC®-certified papers and a range of recyclable HP media with a take-back program³





- Compared with large-format Low Volume LED MFPs with print speeds of up to 7 Arch D pages per minute.

 EPEAT registered where applicable and/or supported. See epeat.net for registration status by country.

 Program availability varies. Please check hp.com/recycle for details. BMG trademark license code FSC®-C115319, see fscorg-com/recycle for details. BMG trademark license code FSC®-C115319, see fscorg-com/recycle for details. BMG trademark license code FSC®-C115319, see fscorg-com/recycle for details. HP trademark license code FSC*-C017543, see fsc.org, Not all FSC*-certified products are available in all regions. For information about HP large format printing materials, please visit globalBMG.com/hp

Please recycle large-format printing hardware and printing supplies Find out how at our website



- 1. With Aurasma installed, please go to the HP DesignJet channel at http://auras.ma/s/ke25m
- 2. Without Aurasma installed, please download it:
 - a. Google Play http://auras.ma/s/android
 - b. Apple Store http://auras.ma/s/ios
 - Once done, go to the HP DesignJet channel at http://auras.ma/s/ke25m
- 3. Open the application and point to the image to view the HP DesignJet video

Technical specifications

Print	Line drawings ³ Print resolution	21 sec/page on A1/D, 120 A1/D prints per hour Up to 2400 x 1200 optimized dpi
	Margins (top x	Roll: $3 \times 3 \times 3 \times 3$ mm (0.12 × 0.12 × 0.12 × 0.12 in) (borderless on photo
	bottom x left x right)	
		Sheet: 3 x 22 x 3 x 3 mm (0.12 x 0.87 x 0.12 x 0.12 in)
	Ink types	Dye-based (C, G, M, pK, Y); pigment-based (mK)
	Ink cartridges	6 (cyan, gray, magenta, matte black, photo black, yellow)
	Line accuracy Minimum line width	+/- 0.1% ⁴ 0.02 mm (0.0008 in) (HP-GL/2 addressable)
		n0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E)) ⁵
	line width	10.07 1111 (0.0020 11) (130) 120 13000.2001(2)
Media	Handling	Input: two automatic front-loading roll feeds; smart roll switching; rolls up to 200 m (650 ft) long each and 180 mm (7.1 in) of diameter; sheet feed Output: integrated output stacker (from A4/A to A0/E, with up to 100
		A1/D-size capacity); media bin; automatic cutter Scanner: straight-through scan paper path for sheet and cardboard originals
	Size	Rolls: 279 to 914 mm (11 to 36 in)
		Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E)
	Thickness	Up to 0.5 mm (19.7 mil)
Scan	Scan speed	Color: up to 6.35 cm/sec (2.5 in/sec)
		Grayscale: up to 19.05 cm/sec (7.5 in/sec)
	Scan/ copy resolution	nUp to 600 dpi
	Maximum scan	Size: 914 x 8000 mm (36 x 315 in) (JPEG)
		914 x 5000 mm (36 x 197 in) (PDF) 610 x 15,000 mm (24 x 590.5 in) (TIFF)
	Thickness	Up to 0.8 mm (0.03 in)
Сору	Reduction/	25 to 400%; at 1% increment
	enlargement	
	Maximum copies	Up to 99 copies
	Copier settings	Copy quality, copy color, roll, paper output, content type, original paper type, background removal, contrast, de-skew, blueprints support, copy
		margin layout, full width, job queue storage mode
Applications	Line drawings, Rende	erings, Presentations, Maps, Orthophotos
Memory	Intel Core i5M-260 pr	ocessor, 128 GB (virtual), ⁶ 500 GB hard disk (AES-256 encrypted,
	FIPS 140-2 Level 2 ce	
Connectivity	Interfaces (standard)	High-Speed USB 2.0 certified host connector Gigabit Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv5, TFTP (IPv4o only), SNMP (v1, v2c, v3), Apple Bonjour Compatible, FTP, WS Discovery, Embedded Web Server(HTTP, HTTPs), IPSec, SMTP (e-mail), Raw IP printing (9100,
	D: 11	9101, 9102), LPD, IPP, WS print, NTLM, NTLM v2, SSL/TLS, 802.1X authentication (WEP, WPA, WPA2, LEAP, PEAP, EAP-TLS)
	Print languages (standard)	HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI
	Print languages	Adobe PostScript 3; Adobe PDF 1.7
	(optional)	
	Printing paths	HP SmartStream software for HP DesignJet printers (optional), Printer driver, HP Embedded Web Server, direct printing from USB flash drive, email printing
	Drivers (included)	HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript,
		PDF Upgrade Kit)
	Printer	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in)
	Printer Shipping	
(w x d x h)	Shipping Printer	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in)
(w x d x h) Weight	Shipping Printer Shipping	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb)
(w x d x h) Weight	Shipping Printer Shipping HP DesignJet T3500	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Multifunction Printer, printhead, introductory ink cartridges, stacker,
(w x d x h) Weight	Shipping Printer Shipping HP DesignJet T3500 scanner calibration s	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Multifunction Printer, printhead, introductory ink cartridges, stacker, neet, printer stand and media bin, spindles, 3-in spindle adapter kit (x2),
(w x d x h) Weight What's in the box	Shipping Printer Shipping HP DesignJet T3500 scanner calibration s	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Multifunction Printer, printhead, introductory ink cartridges, stacker,
(w x d x h) Weight What's in the box Environmental	Shipping Printer Shipping HP DesignJet T3500 scanner calibration sl quick reference guide Operating temperature	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Multifunction Printer, printhead, introductory ink cartridges, stacker, neet, printer stand and media bin, spindles, 3-in spindle adapter kit (x2), setup poster, startup software, power cord 5 to 40°C (41 to 104°F)
(w x d x h) Weight What's in the box Environmental	Shipping Printer Shipping HP DesignJet T3500 scanner calibration sl quick reference guide Operating temperature Storage temperature	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Multifunction Printer, printhead, introductory ink cartridges, stacker, neet, printer stand and media bin, spindles, 3-in spindle adapter kit (x2), setup poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F)
(w x d x h) Weight What's in the box Environmental ranges	Shipping Printer Shipping HP DesignJet T3500 scanner calibration sl quick reference quide Operating temperature Storage temperature Operating humidity	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Multifunction Printer, printhead, introductory ink cartridges, stacker, neet, printer stand and media bin, spindles, 3-in spindle adapter kit (x2), setup poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH
w x d x h) Weight What's in the box Environmental anges	Shipping Printer Shipping HP DesignJet T3500 scanner calibration si quick reference guide Operating temperature Storage temperature Operating humidity Sound pressure	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Multifunction Printer, printhead, introductory ink cartridges, stacker, neet, printer stand and media bin, spindles, 3-in spindle adapter kit (x2), e seturp poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep)
(w x d x h) Weight What's in the box Environmental ranges	Shipping Printer Shipping HP DesignJet T3500 scanner calibration si quick reference quide Operating temperature Storage temperature Operating humidity Sound pressure Sound power	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) Multifunction Printer, printhead, introductory ink cartridges, stacker, neet, printer stand and media bin, spindles, 3-in spindle adapter kit (x2), setup poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); 5.6 B(A) (ready); < 3.4 B(A) (sleep)
(w x d x h) Weight What's in the box Environmental ranges	Shipping Printer Shipping HP DesignJet T3500 scanner calibration si quick reference guide Operating temperature Storage temperature Operating humidity Sound pressure	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Multifunction Printer, printhead, introductory ink cartridges, stacker, neet, printer stand and media bin, spindles, 3-in spindle adapter kit (x2), setup poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 5 od B(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); 5.6 B(A) (ready); < 3.4 B(A) (sleep) <120 watts (printing); < 2 watts (< 7 watts with embedded Digital Front
(w x d x h) Weight What's in the box Environmental ranges	Shipping Printer Shipping HP DesignJet T3500 scanner calibration si quick reference quide Operating temperature Storage temperature Operating humidity Sound pressure Sound power	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) Multifunction Printer, printhead, introductory ink cartridges, stacker, neet, printer stand and media bin, spindles, 3-in spindle adapter kit (x2), setup poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); 5.6 B(A) (ready); < 3.4 B(A) (sleep)
(w x d x h) Weight What's in the box Environmental anges Acoustic	Shipping Printer Shipping HP DesignJet T3500 scanner calibration sl quick reference quide Operating temperature Storage temperature Operating humidity Sound pressure Sound power Consumption	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) Multifunction Printer, printhead, introductory ink cartridges, stacker, neet, printer stand and media bin, spindles, 3-in spindle adapter kit (x2), e, setup poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) <120 watts (printing); < 2 watts (< 7 watts with embedded Digital Front End) (sleep); 0 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A U.S and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (605°T); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico
Dimensions (w x d x h) Weight What's in the box Environmental ranges Acoustic Power Certification	Shipping Printer Shipping HP DesignJet T3500 scanner calibration si quick reference quide Operating temperature Storage temperature Operating humidity Sound pressure Sound power Consumption Requirements	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Multifunction Printer, printhead, introductory ink cartridges, stacker, neet, printer stand and media bin, spindles, 3-in spindle adapter kit (k2), setup poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 1.5 dB(A) (sleep) 6.8 B(A) (printing); 5.6 B(A) (ready); < 3.4 B(A) (sleep) 6.8 (220 watts (printing); < 3 watts (< 7 watts with embedded Digital Front End) (sleep); 0 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A USA and Canada (CSA certified); EU (LVD and EN 60950-1 complaint);
(w x d x h) Weight What's in the box Environmental ranges Acoustic	Shipping Printer Shipping HP DesignJet T3500 scanner calibration siquick reference guide Operating temperature Storage temperature Operating humidity Sound pressure Sound power Consumption Requirements Safety	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 80.4 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Multifunction Printer, printhead, introductory ink cartridges, stacker, neet, printer stand and media bin, spindles, 3-in spindle adapter kit (x2), setup poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); < 2 watts (< 7 watts with embedded Digital Front End) (sleep); 0 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); Korea (KC)
(w x d x h) Weight What's in the box Environmental ranges Acoustic	Shipping Printer Shipping Printer Shipping HP DesignJet T3500 scanner calibration si quick reference quide Operating Emperature Storage temperature Operating humidity Sound pressure Sound power Consumption Requirements Safety Electromagnetic	1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Multifunction Printer, printhead, introductory ink cartridges, stacker, neet, printer stand and media bin, spindles, 3-in spindle adapter kit (x2), setup poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); 5.6 B(A) (ready); < 3.4 B(A) (sleep) 6.8 B(A) (printing); 5.6 B(A) (ready); < 3.4 B(A) (sleep) 120 watts (printing); 2 watts (< 7 watts with embedded Digital Front End) (sleep); 0 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (MYCE); Korea (KC) Compliant with Class A requirements, including: USA (FCC rules), Canada (CES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC) Japan (VCC); Certified as Class A product: Korea (MSIP) ENERGY STAR, WEEE, ROHS (EU, China, Korea, India), REACH, EPEAT

Ordering information

Product	B9E24A	HP DesignJet T3500 36-in Production Multifunction Printer ⁷
	B9E24B	HP DesignJet T3500 36-in Production Multifunction Printer ⁸
Accessories	C0C66A	HP DesignJet PostScript/PDF Upgrade Kit
	G8B09A	HP DesignJet T3500 36-in Spindle
	L3J69AAE	HP SmartStream Preflight Manager
	L3J71AAE	HP SmartStream Preflight Manager One-Year Subscription
	L3J78AAE	HP SmartStream Print Controller for HP DesignJet T3500 Production Multifunction Printer
HP supported accessories	GERA - Ladybird	III online folder
Original HP printheads	B3P06A	HP 727 DesignJet Printhead
Original HP	C1Q13A	HP 764 300-ml Cyan DesignJet Ink Cartridge
ink cartridges	C1Q14A	HP 764 300-ml Magenta DesignJet Ink Cartridge
	C1Q15A	HP 764 300-ml Yellow DesignJet Ink Cartridge
	C1Q16A	HP 764 300-ml Matte Black DesignJet Ink Cartridge
	C1Q17A	HP 764 300-ml Photo Black DesignJet Ink Cartridge
	C1Q18A	HP 764 300-ml Gray DesignJet Ink Cartridge
Original HP large format printing	C6810A	HP Bright White Inkjet Paper (FSC® certified) ⁹ 🛟 10 914 mm x 91.4 m (36 in x 300 ft)
materials	C6980A	HP Coated Paper (PEFC™ certified)³ 🏰 º 914 mm x 91.4 m (36 in x 300 ft)
	C6030C	HP Heavyweight Coated Paper (PEFC™ certified) ⁹ 🛟 10 914 mm x 30.5 m (36 in x 100 ft)
	Q1421B	HP Universal Satin Photo Paper 914 mm x 30.5 m (36 in x 100 ft)
		·

Service and support¹¹

H4518E	HP Installation Service with Network Setup
U1ZX9E	HP 3 year Next Business Day Onsite Support with DMR ¹²
U1ZY0E	HP 5 year Next Business Day Onsite Support with DMR ¹²
U1ZY1PE	HP 1 year Post Warranty, Next Business Day Onsite Support with DMR ¹²
U1ZY2PE	HP 2 year Post Warranty, Next Business Day Onsite Support with DMR ¹²
U1XV4E	HP Preventive Maintenance Service

HP Design let Support Services offer solutions for business critical environments installation, extended support and maintenance, as well as variety of value-added services. For more information, please visit <u>hp.com/go/Designjet/support.</u>

Use Original HP inks and printheads to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system to provide precise line accuracy as well as dark blacks and true neutral grays.¹³ For more information, visit hp.com/go/OriginalHPinks.

For the entire HP Large Format Printing Materials portfolio, please see alobalBMG.com/hp.

Choose from a range of third-party solutions like OpCenter and SCP to streamline your digital printing and scanning operations.

- ¹ Compared with large-format color MFPs under \$25,000 USD. Based on the fastest-rated color speeds as published by manufacturers as of January 2014. Test methods vary.
- Compared with large-format Low Volume LED MFPs with print speeds of up to 7 Arch D pages per minute. Mechanical printing time. Printed in Fast mode, using HP Bright White Inkjet Paper (Bond) and Original HP inks.
- +/- 0.1% of the specified vector length or +/- 0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on AO/E HP Matte Film in Best or Normal mode with Original HP inks.
- Measured on HP Matte Film.
- Based on 2.5 GB RAM.
- 90-day limited hardware warranty.
- 8 Two-year limited hardware warranty.
- BMG trademark license code FSC $^{\circ}$ -C115319, see <u>fsc.org</u>. HP trademark license code FSC $^{\circ}$ -C017543, see <u>fsc.org</u>. BMG trademark license code PEFC $^{\infty}$ /29-31-261, see <u>pefc.org</u>. HP trademark license code PEFC $^{\infty}$ /29-31-198, see <u>pefc.org</u>. Not all FSC $^{\circ}$ or PEFC $^{\infty}$ -certified products are available in all regions.
- $^{\rm 10}$ Can be recycled through commonly available recycling programs.
- 11 HP Service portfolio available only for B9E24B HP DesignJet T3500 36-in Production Multifunction
- ¹² Defective Media Retention keeps your sensitive data safe. To comply with security regulations you can keep the defective hard-drive or data-retentive memory component while getting a new replacement
- ¹³ True neutral grays produced by printers compatible with the HP Three-black ink set.



















For more information, please visit

hp.com/go/designjetT3500

© Copyright 2014-2016 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Adobe, PostScript, and Adobe PostScript 3 are trademarks of Adobe Systems Incorporated. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Intel and the Intel Inside logo are trademarks of Intel Corporation in the U.S. and other countries. Windows is a U.S. registered trademark of Microsoft Corporation. Mac and the Mac logo are trademarks of Apple Computer, Inc., registered in the U.S. and other countries.

